

# SKID TANKS

*For All Purpose, Flexible, Safe Storage for Fuels and Oils*



Clawson offers several types of aboveground single- and double-wall skid tanks. Heavy-duty Skid Tanks combine mobility with structural

integrity for highly flexible and safe storage. Economy Skid Tanks are built to provide safe and dependable stationary storage. In addition to standard skid

tanks, Clawson manufactures UL labeled models. Available in either red or green enamel, Skid Tanks have capacities ranging from 300 to 2,100 gallons and are compatible with a wide range of fuels.

To meet secondary containment requirements, heavy-duty steel dikes are available.

## Single Wall

Capacity	Diameter	Length	NON-UL LISTED		UL LISTED	
			Thickness	Economy Heavy-Duty	Thickness	Economy Heavy-Duty
160-gallon	38"	30"	14-ga	195 lbs 350 lbs	12-ga	250 lbs 350 lbs
300-gallon	38"	60"	14-ga	270 lbs 540 lbs	12-ga	360 lbs 540 lbs
560-gallon	48"	72"	12-ga	540 lbs 850 lbs	12-ga	540 lbs 850 lbs
1,000-gallon	48"	128"	10-ga	N/A 1,650 lbs	10-ga	1,080 lbs 1,650 lbs
1,100-gallon	48"	144"	12-ga	940 lbs N/A	N/A	N/A N/A
2,000-gallon	64"	144"	7-ga	N/A 2,600 lbs	7-ga	2,200 lbs 2,600 lbs

## Double Wall—UL Listed

Capacity	Diameter	Length	Thickness	Economy Style	Heavy-Duty Style
160-gallon	38"	30"	12 gauge	450 lbs	550 lbs
300-gallon	38"	60"	12 gauge	660 lbs	840 lbs
560-gallon	48"	72"	12 gauge	1,020 lbs	1,330 lbs
1,000-gallon	48"	128"	10 gauge	2,000 lbs	2,570 lbs
2,000-gallon	64"	144"	7 gauge	N/A	4,100 lbs

**Standard Fittings:** Standard tanks come with the following: on 160- and 300-gallon, (one) 1" drain, one (1) 1-1/2", three (3) 2"; 560-gallon, one (1) 1" drain, four (4) 2"; and 1,000- and 2,000-gallon, one (1) 1" drain, three (3) 2", one (1) 3" fittings. UL 142 listed skid tanks require an additional emergency vent fitting (560-gallon and smaller, 4"; 1,000-gallon and 2,000-gallon, 6"). Double-wall tanks require an interstice emergency vent and monitoring fitting.



4545 Clawson Tank Drive  
Clarkston, Michigan 48346  
248-625-8700 • Fax: 248-625-3066

**1-800-272-1367**